

Product Bulletin

CV3-3.0-OL/53#

TRAFFIC GRAFFIC[®] OVERLAMINATE

A 3.0 mil clear flexible calendared vinyl film designed for use as a short term protective overlay for Traffic Graff[®] decals. Adhesive 200-4990 is a permanent acrylic pressure sensitive adhesive formulated for exceptional clarity and bond for this type application.

Applications	This product is intended for use as the overlaminating film to produce short term Traffic Graff [®] floor decals. The adhesive is formulated to adhere to most common printing inks. However, specific formulations must be tested before use. Some inks may contain excessive flow additives that could reduce adhesion of this product. Test before production.	
Slip Resistance	CVE-3.0-OL/53# is classified under UL 410 for floor graphics overlay applications.	
Thickness	Film Adhesive Liner (Thickness variation +/- 10%)	3 mils. .8 to 1.1 mils. 4 mils.
Temperature Ranges	Minimum application temperature Service temperature	+40°F. -40°F to +200°F.
Expected Exterior Exposure	This product is designed for interior applications.	
Durability	CV3 will function as a floor overlaminate for three (3) months under normal use.	
Adhesion	To stainless steel Tested according to PSTC-101 Method A with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	40 oz/in.
Water Resistance	Good	
Humidity Resistance	Excellent	
Storage Stability	6 months shelf life when stored at 70°F and 50% relative humidity.	
Product Code	CVE-3.0-OL/53#	



**Manufacturer of Pressure Sensitive Films,
Traffic Graff Floor Advertising Films,
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.