

TECHNICAL DATA SHEET

GF 201 3.4 MIL MATTE WHITE VINYL CLEAR PERMANENT ADHESIVE

GF 201 is a 3.4 mil polymeric matte white calendered vinyl coated with a clear permanent acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl is designed to accept a variety of solvent-based, eco-solvent, latex and UV curable inks common to wide format digital printing systems. The clear adhesive creates a permanent bond to a variety of common substrates used in graphics applications. The 90# liner provides excellent layflat qualities in a variety of ambient conditions along with ease of application of large format graphics.

PRODUCT NAME	201
FILM	
Film Type	White Polymeric Vinyl
Film Thickness (mils/ μ m)	3.4 / 86 (+/- 10%)
Film Weight (gsm)	120
Gloss (60°)	< 20
Opacity (%)	93
Tensile Strength (lbs/in)	MD > 3000 / CD > 2600
Elongation (%)	MD > 90 / CD > 150
Dimensional Stability (FTM 14)	MD < 1.00 mm / CD < 0.50 mm
ADHESIVE	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils/ μ m)	0.8-1.0 / 20-25
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.0 / 13
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	4.0 / 18
LINER	
Liner Weight (#/gsm)	90 / 145 (+/- 10%)
Liner Type	White 2-sided PE-Coated Kraft
Liner Thickness (mils/ μ m)	6.7 / 170
Release Force @ 300" / min (g/2")	50-80
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	up to 5 years

TECHNICAL DATA SHEET

GF 201 - 3.4 MIL MATTE WHITE VINYL CLEAR PERMANENT ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p>APPLICATION</p> <ul style="list-style-type: none"> <input type="radio"/> WET APPLY <input checked="" type="radio"/> DRY APPLY <input type="radio"/> LAMINATING <input type="radio"/> MOUNTING <input checked="" type="radio"/> DIE CUTTABLE <input type="radio"/> HOT STAMP <input type="radio"/> THERMAL DIE <input checked="" type="radio"/> FLATBED CUTTABLE 	<ul style="list-style-type: none"> <input checked="" type="radio"/> POP/RETAIL <input type="radio"/> WALL <input type="radio"/> WRAP <input checked="" type="radio"/> WINDOW <input type="radio"/> FLOOR <input type="radio"/> FLEET <input type="radio"/> TRANSLUCENT <input checked="" type="radio"/> GENERAL SIGNAGE <input type="radio"/> OUTDOOR (SHORT TERM) <input checked="" type="radio"/> OUTDOOR (LONG TERM) 	<ul style="list-style-type: none"> <input checked="" type="radio"/> SOLVENT <input checked="" type="radio"/> ECO-SOLVENT <input checked="" type="radio"/> LATEX <input checked="" type="radio"/> UV CURABLE <input checked="" type="radio"/> SCREEN <input checked="" type="radio"/> OFFSET (UV CURABLE) <input type="radio"/> OFFSET (CONVENTIONAL)
<p>SUBSTRATES</p> <ul style="list-style-type: none"> <input checked="" type="radio"/> OEM PAINTED METAL <input checked="" type="radio"/> PAINTED ALUMINUM <input checked="" type="radio"/> STAINLESS STEEL <input type="radio"/> LOW-ENERGY SURFACES <input checked="" type="radio"/> ACRYLIC <input checked="" type="radio"/> GLASS <input type="radio"/> POLYESTER 		

FAQS

What applications is GF 201 intended for?	GF 201 is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.
Can GF 201 be removed?	Most decals can be removed with some effort, even if they have a permanent adhesive. GF 201 has a standard clear permanent adhesive that works on a variety of surfaces. The adhesive will not remove cleanly, but any adhesive transfer or residue can be cleaned up easily with standard adhesive removers.