


**TECHNICAL
DATA
SHEET**
**VFWQS-NTC-AR/84
SCREEN & OFFSET**
**3.4 MIL MATTE WHITE VINYL
CLEAR REMOVABLE ADHESIVE**

VFWQS (Quick-Split) is a 3.4 mil matte white flexible calendered vinyl film coated with a clear removable acrylic pressure sensitive adhesive laminated to a 84# quick-split liner. This film is designed to accept a variety of UV curable and solvent-based screen inks. This product is recommended for decals, nameplates and signage where a high quality marking film requiring flexibility, durability and resistance to sunlight is required.

| PRODUCT NAME | VFWQS-NTC-AR/84 |
|---|--------------------------|
| FILM | |
| Film Type | Matte White Vinyl |
| Film Thickness (mils/ μ m) | 3.4 / 85 (+/- 10%) |
| Film Weight (gsm) | 120 |
| Gloss (60°) | \geq 20 |
| Opacity (%) | 93 |
| ADHESIVE | |
| Adhesive Type | Removable |
| Adhesive Thickness (mils/ μ m) | 0.8-1.0 / 20-25 |
| Adhesive Color | Clear |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min | 1.5 / 6.6 |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs | 2.3 / 10 |
| LINER | |
| Liner Weight (#/gsm) | 84 / 135 (+/- 10%) |
| Liner Type | Quick-split scored liner |
| Liner Thickness (mils/ μ m) | 6.7 / 170 |
| Release Force @ 300" / min (g/2") | 40-70 |
| PERFORMANCE GUIDANCE | |
| Application Temperature | \geq +40 °F |
| Service Temperature | -40 °F to 180° F |
| Shelf Life | 1 year |
| Storage Temp / Rel. Humidity | 70 °F / 50% |
| Outdoor Durability | 5 years |
| Removability | 1 year |

**All values provided are typical averages intended for guidance only and should not be interpreted as product specifications or warranties.*



IF SHEETED, SCORE DIRECTION ON THE LINER IS INDICATED BY THE "SLD" (SCORE LINE DIRECTION) OR LAST DIMENSION OF THE SHEET SIZE. UNIVERSAL SPLIT/SCORE SPACING IS 1.25"