

**TECHNICAL
DATA
SHEET**
**VFLC-NTC-AP/90
SCREEN & OFFSET**
**3.0 MIL LUSTRE CLEAR VINYL
CLEAR PERMANENT ADHESIVE**

A 3.0 mil lustre clear flexible calendered vinyl film coated with permanent acrylic pressure sensitive adhesive on a 90# layflat liner. This film accepts a variety of UV curable and solvent-based screen inks. Designed for signage, decals, nameplates, die-cut letters and point-of-purchase displays.

PRODUCT NAME	VFLC-NTC-AP/90
FILM	
Film Type	Lustre Clear Vinyl
Film Thickness (mils/ μ m)	3.0 mil / 76 μ m (+/- 10%)
Film Weight (gsm)	95
Gloss (60°)	30-50
Opacity (%)	Not applicable
ADHESIVE	
Adhesive Type	Permanent
Adhesive Color	Clear
Adhesive Thickness (mils/ μ m)	0.8-1.1 mil / 20-28 μ m
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.8 / 17
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	4.8 / 21
LINER	
Liner Weight (#/gsm)	90 / 145 (+/- 10%)
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/ μ m)	6.7 mil / 170 μ m
Release Force @ 300" / min (g/2")	50-100
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 degrees F
Service Temperature	-40 to 180 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Up to 3 years