

**TECHNICAL
DATA
SHEET**
GF 365
**3.0 MIL GLOSS WHITE VINYL
CLEAR PERMANENT ADHESIVE**

GF 365 is a 3.0 mil gloss white vinyl with a clear acrylic pressure sensitive adhesive on a 75# 2-sided poly-coated liner. This calendared vinyl is designed to accept a variety of solvent, eco solvent, latex and UV curable inks common to wide format digital printing systems. The adhesive produces permanent bonds to a variety of common substrates used in graphic applications short term.

PRODUCT NAME	365
FILM	
Film Type	White Monomeric Vinyl
Film Thickness (mils/ μ m)	3.0 / 76 (+/- 10%)
Film Weight (gsm)	105
Gloss (60°)	\geq 70
Opacity (%)	93
Tensile Strength (lbs/in)	MD \geq 3800 / CD \geq 3500
Elongation (%)	MD \geq 180 / CD \geq 200
Dimensional Stability (FTM 14)	MD \leq 1.5 mm / CD \leq 1.0 mm
ADHESIVE	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils/ μ m)	0.7-1.0 / 18-25
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.5 / 15
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	5.0 / 22
LINER	
Liner Weight (#/gsm)	75 / 120
Liner Type	White 2-Sided Poly-Coated Kraft
Liner Thickness (mils/ μ m)	5.0 / 125
Release Force @ 300" / min (g/2")	40-90
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	up to 3 years

TECHNICAL DATA SHEET

GF 365 - 3.0 MIL GLOSS WHITE VINYL CLEAR PERMANENT ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p>APPLICATION</p> <ul style="list-style-type: none"> <input checked="" type="radio"/> WET APPLY <input checked="" type="radio"/> DRY APPLY <input type="radio"/> LAMINATING <input type="radio"/> MOUNTING <input checked="" type="radio"/> DIE CUTTABLE <input type="radio"/> HOT STAMP <input type="radio"/> THERMAL DIE <input checked="" type="radio"/> FLATBED CUTTABLE 	<ul style="list-style-type: none"> <input checked="" type="radio"/> POP/RETAIL <input type="radio"/> WALL <input type="radio"/> WRAP <input type="radio"/> WINDOW <input type="radio"/> FLOOR <input type="radio"/> TRANSLUCENT <input type="radio"/> FLEET <input checked="" type="radio"/> GENERAL SIGNAGE <input checked="" type="radio"/> OUTDOOR (SHORT TERM) <input type="radio"/> OUTDOOR (LONG TERM) 	<ul style="list-style-type: none"> <input checked="" type="radio"/> SOLVENT <input checked="" type="radio"/> ECO-SOLVENT <input checked="" type="radio"/> LATEX <input checked="" type="radio"/> UV CURABLE <input checked="" type="radio"/> SCREEN <input checked="" type="radio"/> OFFSET (UV CURABLE) <input type="radio"/> OFFSET (CONVENTIONAL)
<p>SUBSTRATES</p> <ul style="list-style-type: none"> <input checked="" type="radio"/> OEM PAINTED METAL <input checked="" type="radio"/> PAINTED ALUMINUM <input checked="" type="radio"/> STAINLESS STEEL <input type="radio"/> LOW-ENERGY SURFACES <input type="radio"/> ACRYLIC <input type="radio"/> GLASS <input type="radio"/> POLYESTER 		

FAQS

What applications are GF 365 intended for?	GF 365 is designed for short-term interior or exterior signage, decals, nameplates, point-of-purchase displays and general signage. This product is not intended for vehicle applications.
Can GF 365 be removed?	Most decals can be removed with some effort, even if they have a permanent adhesive. GF 365 has a standard permanent adhesive that works on a variety of surfaces. This adhesive is permanent and will not remove cleanly, but any adhesive transfer or residue can be cleaned up easily with standard adhesive removers.