

**TECHNICAL
DATA
SHEET**
**VFGW-NTC-AP/90
SCREEN & OFFSET**
**3.0 MIL GLOSS WHITE VINYL
CLEAR PERMANENT ADHESIVE**

A 3.0 mil gloss white calendered vinyl film coated with a clear permanent acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl is designed to accept a variety of solvent-based, eco-solvent, latex and UV curable inks. The clear adhesive creates a permanent bond to a variety of common substrates used in graphics applications. The 90# liner offers excellent product layflat in a variety of ambient conditions. This product is designed for permanent decals, nameplates, product markings and point-of-purchase decals.

PRODUCT NAME	VFGW-NTC-AP/90
FILM	
Film Type	Gloss White Vinyl
Film Thickness (mils/ μ m)	3.0 mil / 76 μ m (+/- 10%)
Film Weight (gsm)	105
Gloss (60°)	\geq 80
Opacity (%)	94
ADHESIVE	
Adhesive Type	Permanent
Adhesive Color	Clear
Adhesive Thickness (mils/ μ m)	0.8-1.0 mil / 20-25 μ m
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	2.5 / 11
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	4.0 / 18
LINER	
Liner Weight (#/gsm)	90 / 145 (+/- 10%)
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/ μ m)	6.7 mil / 170 μ m
Release Force @ 300" / min (g/2")	50-80
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 degrees F
Service Temperature	-40 to 180 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Up to 5 years