

**TECHNICAL
DATA
SHEET**
**VFW-NTC-ARLT/96
SCREEN & OFFSET**
**3.4 MIL MATTE WHITE VINYL
CLEAR LOW-TACK REMOVABLE ADHESIVE**

A 3.4 mil matte white flexible calendared vinyl film coated with low-tack removable acrylic pressure sensitive adhesive on a 96# layflat liner that offers a printable surface on the backside. This film is designed to accept a variety of UV curable and solvent-based screen inks. The layflat liner is coated on the backside to offer adhesion to solvent screen, UV screen, offset and letterpress ink but must be tested with specific ink prior to use. This product is designed for temporary decals applied to windows.

PRODUCT NAME	VFW-NTC-ARLT/96
FILM	
Film Type	Matte White Vinyl
Film Thickness (mils/ μ m)	3.4 mil / 86 μ m (+/- 10%)
Film Weight (gsm)	120
Gloss (60°)	\geq 20
Opacity (%)	93
ADHESIVE	
Adhesive Type	Removable
Adhesive Color	Clear
Adhesive Thickness (mils/ μ m)	0.8-1.0 mil / 20-25 μ m
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	0.09-0.30 / 0.4-1.3
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	0.09-0.50 / 0.4-2.2
Peel Strength on Glass (lbs/in / N/25mm) 15 min	0.20-0.50 / 0.9-2.2
Peel Strength on Glass (lbs/in / N/25mm) 24 hrs	0.20-0.50 / 0.9-2.2
LINER	
Liner Weight (#/gsm)	90 / 145 (+/- 10%)
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/ μ m)	6.7 mil / 170 μ m
Release Force @ 300" / min (g/2")	20-50
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 degrees F
Service Temperature	-40 to 180 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Up to 5 years
Long-Term Removability	Up to 1 year