

TECHNICAL DATA SHEET VFW-TC-R/90 SCREEN & OFFSET 3.4 MIL MATTE WHITE VINYL CLEAR HIGH-TACK REMOVABLE ADHESIVE

A 3.4 mil polymeric matte white calendered vinyl coated with a high performance removable solvent acrylic pressure sensitive adhesive on a 90# layflat liner. This product was specifically designed to adhere to common commercial carpets and allow for easy and clean removability of the graphic. These are carpets with a short nap with a tight weave containing minimal texture. The 90# liner offers excellent product layflat in a variety of ambient conditions. This film is topcoated for conventional offset printing. The base vinyl must be overlaminated to provide protection to the graphics in the Traffic Graphic® application.

PRODUCT NAME	V F W - T C - R / 9 0
FILM	
Film Type	Matte White Vinyl
Film Thickness (mils/µm)	3.4 mil / 86 μm (+/- 10%)
Film Weight (gsm)	120
Gloss (60°)	40-50
Opacity (%)	93
ADHESIVE	
Adhesive Type	Removable
Adhesive Color	Clear
Adhesive Thickness (mils/µm)	0.7-0.9 mil / 18-23 μm
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.0 / 13
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	4.5 / 20
LINER	
Liner Weight (#/gsm)	90 / 145 (+/- 10%)
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/µm)	6.7 mil / 170 μm
Release Force @ 300" / min (g/2")	50-80
PERFORMANCE GUIDANCE	
Application Temperature	\ge +40 degrees F
Service Temperature	-40 to 180 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Indoor only
Long-Term Removability	Up to 6 months

VFW-TC-R/90 | JAN 2024

309 S. UNION | SPARTA, MI 49345 | P:(616) 887-7387 | T:(800) 253-3664 | F:(616) 887-0537